

全显示效果图

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
COM1	5F	5A	6F	6A	7F	7A	S4	S5	10A	10F	9A	9F	8A	8F	COM1							
COM2	5G	5B	6G	6B	7G	7B	S3	S6	10B	10G	9B	9G	8B	8G		COM2						
COM3	5E	5C	6E	6C	7E	7C	S2	S7	10C	10E	9C	9E	8C	8E			COM3					
COM4	5D	5P	6D	6D	P7	7D	S1	S8	10D	S14	9D	8D	S10				COM4					
COM5	1F	1A	2F	2A	3F	3A	4F	4A		X14	X13	X6	X5	S9				COM5				
COM6	1G	1B	2G	2B	3G	3B	4G	4B	X19	X15	X12	X7	X4	S11				COM6				
COM7	1E	1C	2E	2C	3E	3C	4E	4C	X18	X16	X11	X8	X3	S12				COM7				
COM8		ID	P2	2D	P3	3D	P4	4D	X1	X17	X10	X9	X2	S13						COM8		

NOTICE: REFERENCES UNLESS OTHERWISE

SPECIFIED: ±0.2

2 ALL DIMENSIONS ARE IN mm

3 VIEWING ANGLE:12'CLOCK

4 POLARIZER:REFLECTIVE,POSITIVE

5 MULTIPLEX LEVEL: 1/8 DUTY, 1/4 BIAS

6 LCD DRIVING VOLTAGE(Vop):3.15V

7 OPERATING TEMP: -40°C TO 70°C

STORAGE TEMP: -40°C TO 80°C

8 DISPLAY TYPE: HTN

9 CONNECTOR: PIN

10 GLASS THICKNESS: FRONT--1.1

BACK --1.1



11 MATERIAL CONFORM TO THE ROHS STANDARD

WITH SCREEN PRINTING

Eff.Data	Rev.	Change Description
2014-06-19	A	11版改储存温度 12版改反射, 3.15V, 视角12点, 工作温度, 储存温度, 图案, 逻辑
2014-06-20	B	
2014-06-24	C	

Dalian Good Display,Ltd

DESIGN MODEL		GDC03077	
REV.	C	DATE	2014.06.24
CUSTOMER MODEL		APPROVED BY	SY ZHAO
		CHECKED BY	SY ZHAO
PAGE	1/2	DRAWN BY	LJ WANG



SEG

COM

Eff.Date	Rev.	Change Description
2014-06-19	A	new
2014-06-20	B	11版改储存温度
2014-06-24	C	12版改反射, 3.15V, 视角12点, 工作温度, 储存温度, 图案, 逻辑

Dalian Good Display Co.,Ltd

DESIGN MODEL		GDC03077	
REV.	C	DATE	2014.06.24
CUSTOMER MODEL		APPROVED BY	SY ZHAO
		CHECKED BY	SY ZHAO
PAGE	2/2	DRAWN BY	LJ WANG